

Nr. 01-14-0065-001-01

# Declaration of Performance

Version: 06/2015 – Nr. 1

<b>1. Unique identification code of the product-type:</b>	Coating/Finishing plaster	
<b>2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):</b>	322 – Hey'di Grå	
<b>3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:</b>	Cement based and diffusion open decorative coating/wash for masonry and concrete.	
<b>4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):</b>	Hey'di AS, Postboks 13, 2017 Frogner. heydi@heydi.no	
<b>5. When applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):</b>	Not relevant	
<b>6. Systems or systems of assessment and verification of constancy of the construction product as set out in CPR, Annex V:</b>	System 2+	
<b>7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:</b>	Kontrollrådet No. 1111, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificates of conformity of the factory production control No. 1111-CPD-0559	
<b>8. Declared performance</b>	Not relevant	
<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical specification</i>
Adhesion	>0,5 N/m m <sup>2</sup> – FP=B	NS-EN 998-1
Thermal conductivity/densitet	0,82 W/m·K ( $\lambda_{10,dry,mat}$ P=50%, table value A.12, NS-EN 1745)	NS-EN 998-1
Water absorption	W1	NS-EN 998-1
Water vapour permeability	$\mu$ 15/35 (table value A.12, NS-EN 1745)	NS-EN 998-1
Durability	Structures in moderate environment	NS-EN 998-1



Dangerous substances	No hazardous substances	NS-EN 998-1
Resistance to fire	A1	NS-EN 998-1

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Frogner,  
18.06.15

R & D Manager  
Bjørn Bonsak

A handwritten signature in blue ink, which appears to read "Bjørn Bonsak". The signature is written in a cursive style.

Sted/dato

Navn/stilling

Signatur